



Braille Battery™ MICRO-LiTE™ Lithium Technology

Lighter. Stronger. Faster.

Part Number: B128L
Model Name: Braille MICRO-LiTE B128L Lithium Technology Racing Battery




- NEW FOR 2016: MORE CRANKING POWER, LOWER IMPEDANCE DESIGN
- Easy Install: Built in a Direct Replacement Size
- Safe: Sealed Safe Design, Proven Performance
- Fast Power: Rapid Recharge, Stable Voltage Output
- Greener: Modular Design For Longer Life
- Exclusive Braille Lithium Racing Warranty

PHYSICAL SPECS

BCI Group: Same Length as Group 24, 27 & 34
 Length: 10.0" / 254 mm
 Width: 3.25" / 82.5 mm
 Height: 6.00" / 152.4 mm
 Minimum Weight: 8.3 lbs / 3.76 kg
 Post Type: Braille True Torque SAE Auto Posts, 3/8" bolt top. Threaded Stud
 Also Available
 Recommended Mount: Secure Mounting with Vibration padding.
 Braille #211 Optional



New Stud Terminal



Optional OEM Terminal

PERFORMANCE

Voltage : 12 volts
 Full Charge Range: 13.6 - 13.8 volts
 Cranking Amps : 1698
 Lead-Acid Equivalent Capacity: 90 Lithium AH (LAH)
 Nominal Capacity (C/20 rate): 30 AH
 Impedance: < 4.0 milliohms
 Life Cycle @ 10% DOD: Up to 5000 cycles
 Life Cycle @ 80% DOD: Up to 2000 cycles

CHARGING & USAGE INFORMATION

Alternator: Automotive & Marine Compatible
 Battery charger: Model # 12310L & 12325L
 Rapid Recharge: 25 AH electronically controlled
 Recommended Charge Voltage: 14.4 - 14.8 Volts
 Do Not Exceed Charge Voltage: Up to 15 Volts
 Minimum Recommended Voltage: 8.0 Volts

WARRANTY

Warranty: 1 Year Free repair/replacement. See warranty terms and conditions.



braille
BATTERY
 LIGHTER • STRONGER • FASTER
 a GRAFOID company

*Performance specifications denote maximum lead-acid equivalents. Actual performance may vary. Pricing, specifications and features current as of 1/16, subject to change without notice. For latest information, contact Braille directly.
 Braille Battery, Sarasota, FL 34243 USA Toll Free: 1-800-764-4708 Ph: 941-312-5047 Fax: 941-870-3381 Email: sales@braillebattery.com
 Web: www.braillebattery.com Copyright Braille Battery 2016 Braille MICRO-LiTE B128L Spec Data 1.16