

Braille Battery[™] Advanced AGM[™] B14115 Lightweight Battery

Lighter. Stronger. Faster



PHYSICAL SPECS

Replacement Group: Length: Width: Height: Minimum Weight (lbs): Terminals: Auto Posts: Polarity: Recommended Mounts:

PERFORMANCE

Voltage Class: Full Charge Range: Max Amps: Pulse Cranking Amps: Cranking Amps @ 32F: Cranking Amps @ 0F: Nominal Capacity: Internal Resistance (ohms): Life Cycle @ 10% DOD:

CHARGING INFORMATION

Alternator: Battery charger: **Rapid Recharge:** Maximum Charge Voltage @70F: **Recommended Charge Voltage:**

WARRANTY

Warranty:

- Easy Install: Usable for all Group Sizes, Drop In Replacement
- Faster: Up to 40% Lighter, Less HP Loss
- Safer: Sealed Safe Design, Non-Spilling
- Efficient: Stable Voltage Output, Less Stress on Alternator
- Greener: Constructed from Premium Recycled Materials
- Reliable: Individually Certified, Racing Warranty, Made in USA

Usable for all Group Sizes 5.8" / 150 mm 3.4" / 86.4 mm 5.8" / 147.3 mm 11.5 lbs / 5.175 kg Vertical or Horizontal TrueTorque SAE Auto Posts Left Positive # 1418, 211, 6186, 6188, 61810

> 12 volts 13.8 volts 2200 904 486 360 15 AH < 5.5 milliohms (.00550hms) 1500 cycles

Automotive, Marine and Cycle Compatible Braille Model 1232, 1236, 12310 Yes, 10-20 amp electronically controlled 30 amp/hr 14.8 - 15.2 Volts

12 Month Limited Warranty



Actual performance may vary. Pricing, specifications and features calculated as of 5/16, subject to change without notice. For latest information, contact Braille directly Braille Battery, Sarasota, FL USA Ph: 941-312-5047 Fax: 941-870-3381 Email: sales@braillebattery.comWeb: www.braillebattery.com Copyright Braille Battery, Inc 2014 Braille AAGM Lighweight Spec Data 1.17 y.comWeb: www.braillebattery.com Braille AAGM Lighweight Spec Data 1.17



Braille B14115 Model Shown *w/ TrueTorque*TM *Terminals* attached