


IC800-24

Automatic 24V 8A 7 Stage Battery Charger


A highly advanced charger for all your 24V battery requirements. Capable of being set to perfectly suit the specific battery chemistry type as well as offering an adjustable charge rate feature to match a large range of battery sizes.



Removable Clamp for Hard-Wiring

Temperature Compensation Probe

FEATURES




Multi-Chemistry

Set the charging profile to suit battery chemistry type: Wet, Calcium, AGM or Gel



Adjustable Output

Adjustable for different battery sizes and includes temperature compensation probe for precise charging (Details page 35)



Power Supply Mode

Maintains a constant voltage on a battery making it ideal for vehicle diagnostics



Wired Remote Control

Allows charger to be mounted out of sight yet retain total control (Details page 35)



Shock & Dust Proof

Durable construction and safer charging with spark free and polarity protected connection

SPECIFICATIONS

PRODUCT DETAILS		L.E.D AND LCD CHARGE INDICATION			
PART NO.	IC800-24	SCREEN	Back lit LCD screen		
TYPE	7 stage	• RED LIGHT ON	Power on		
INPUT	240VAC, 50Hz, 480W	• BLUE LIGHT ON	Charging		
OUTPUT	24V	• GREEN LIGHT ON	Fully charged and maintaining, no need to turn the charger off		
OUTPUT CURRENT	2, 4, 6, 8A	BATTERY CHARGE TIMES			
MINIMUM START VOLTAGE	4.5V	IC800-24	VOLTAGE	BATTERY SIZE	CHARGE TIME
BACK DRAIN	5mA	AUTOMOTIVE	24V	80–1000CCA	7–24 hrs
APPROVALS	Electrical Safety, EMC	MARINE	24V	110–1300MCA	7–24 hrs
CHARGE VOLTAGE	28.2V (GEL), 28.8V (AGM), 29.4V (WET), 32.0V (CALCIUM)	DEEP CYCLE	24V	14–160Ah	7–24 hrs

APPLICATIONS

Ideal Battery Types



Vehicles



REPLACEMENT PARTS ICTEMP Temperature compensation probe ICREMOTE Remote control